


TRACK LINE M 3PH. 80 830/835/840 DWB ML | BK DALI

TRACK LINE M, 3~ Spot, 80 830/835/840 DWB ML BK DALI

The TRACK LINE M 3~ Spot is a three-phase spotlight suitable for indoor use. Typical applications include commercial and public spaces where flexible and directed lighting is required. The luminaire offers a light output ranging from 4,300 to 8,000 lumens and features a DALI-2 dimming function that allows for stepless control of light intensity. The housing is made of aluminium, complemented by optical elements made of PMMA, and measures 115.2 cm in length, 6.47 cm in width, and 7 cm in height. The IP20 protection rating indicates protection against solid foreign objects larger than 12.5 mm, while the impact resistance corresponds to IK02 class. The combination of robust materials and modern control technology makes the spotlight suitable for a wide range of lighting requirements.



Item no.	1011591
IP Code	IP20
Impact resistance class	IK02
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	200-350mA
Safety class	I
Wattage	27 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	19.0
Number of luminaires at LS C16A	32.0
Level of inrush current	16.63 A
Duration of inrush current	330 µs
Beam angle	120°
Color	black
CRI	80
LXXBXX data	L80B10
Service life	100 000 h
Length	115.2 cm
Width	6.5 cm
Height	7 cm
Net weight	1.11 kg
Gross weight	1.21 kg