


RETRO LT 1500 135 835/840/850 MB ML EM 3H WH | LICHTRÄGER 1500

RETRO, LT 1500 135 835/840/850 MB ML EM 3H WH LICHTRÄGER 1500

The RETRO LED trunking system is specifically designed for the tool-less and time-saving upgrade of existing T8 and T5 fluorescent lamps. The light supports with integrated emergency light function (3h) ensure additional safety in the event of a power failure. With a multi-colour function (3000 K/4000 K/5000 K), various beam characteristics (NB/MB/WB/Oval) and optional DALI control, they offer maximum flexibility when upgrading existing installations.



Item no.	1011653
IP Code	IP20
Impact resistance class	IK04
Assembly	Track
Assembly details	Ceiling,
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	200-550mA
Safety class	I
Wattage	26 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	20.0
Number of luminaires at LS C16A	32.0
Level of inrush current	22.31 A
Duration of inrush current	248 µs
Color	white
CRI	80
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	1
Length	147.5 cm
Width	6.5 cm
Height	3.5 cm
Net weight	1.88 kg
Gross weight	2.01 kg