
MEDO 2 SLIM 40 | CL, DALI

MEDO 2 SLIM 40, CL, DALI, Ceiling Surface-Mounted Luminaire, 3000/4000 K, 15.5 W, 85°, white

The MEDO 2 SLIM 40 is a surface-mounted ceiling luminaire suitable for indoor use, for example in offices or public buildings. It provides a luminous flux of 1900 lumens with a colour temperature of 3000 or 4000 Kelvin and a beam angle of 85 degrees. The luminaire is equipped with DALI 2 and touch dimming, allowing flexible light control. The housing is made of aluminium and steel, measures 38 centimetres in diameter, and has a height of 4.9 centimetres. The IP20 protection rating and IK03 impact resistance ensure safe use in protected indoor areas.



Item no.	1011704
IP Code	IP20
Impact resistance class	IK03
Assembly	Surface
Assembly details	Ceiling,Wall,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	40
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	400 mA
Safety class	I
Wattage	16 W
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	37.0
Number of luminaires at LS C16A	62.0
Level of inrush current	24 A
Duration of inrush current	98 µs
Beam angle	85°
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L80B10
Service life	100 000 h
Risk Group	0
Height	4.9 cm
Diameter	38 cm
Net weight	3.3 kg
Gross weight	4.2 kg
BIG WHITE Page	201

Accessories

1011779	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, black
1011780	MEDO 2 SUSPENSION KIT, 1.5 m Pendant Length, Central, white
1011781	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, black
1011782	MEDO 2 SUSPENSION KIT, 5 m Pendant Length, Central, white
1011783	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, black
1011784	MEDO 2 SUSPENSION KIT, 3 m Pendant Length, Parallel, white