


ENOLA 2.0 M | 3PH., SINGLE, GU10, QPAR51

ENOLA 2.0 M, 3~ Spot, SINGLE, QPAR51, 1 x 10 W, white

The 3~ spot from the ENOLA 2.0 product line is designed for mounting on ceiling and wall track systems, making it ideal for flexible indoor lighting solutions. The housing is made of aluminium, while the diffuser is manufactured from polycarbonate. With compact dimensions of 10.6 cm in length, 5.8 cm in diameter, and 8.5 cm in height, the luminaire offers a space-saving design. The IP20 protection rating and IK02 impact resistance ensure reliable operation in protected environments. The luminaire is designed for GU10 lamps with QPAR51 sockets and supports a three-phase power supply. This product is particularly suitable for use in professional lighting installations where flexible and precise light control is required.



Item no.	1011712
Socket	GU10
Number of sockets	1
Tilt range	90°
Horizontal rotation range	330°
IP Code	IP20
Impact resistance class	IK02
Assembly	Track
Assembly details	Ceiling,Wall,
Primary nominal voltage	220-240V ~ 50/60Hz
Safety class	II
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Color	white
Length	10.6 cm
Height	8.5 cm
Diameter	5.8 cm
Net weight	0.16 kg
Gross weight	0.26 kg
BIG WHITE Page	565

Recommended light bulbs

1005076	LED lightbulb QPAR51, GU10, 2700 K, white
1012469	LED PAR16 Smart, GU10, Tunable White, Zigbee

Accessories

1011749	ENOLA 2.0/BIMA 2.0 M, Decorative ring, Ø 54 mm, black
1011750	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, white
1011751	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, gold
1011752	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, copper