


ENOLA 2.0 M | 3PH., PD, SINGLE, GU10, QPAR51

ENOLA 2.0 M, 3~ pendant luminaire, SINGLE, QPAR51, 1 x 10 W, white

The ENOLA 2.0 M is a 3~ pendant luminaire suitable for indoor lighting. It is designed for track pendant mounting and features a suspension length of 200 centimetres. The housing is made of aluminium and polycarbonate, ensuring a robust construction. The luminaire is equipped with a QPAR51 socket for a 10-watt lamp. With a product diameter of 5.8 centimetres and a height of 10.5 centimetres, it offers a compact design. The protection rating is IP20, and the impact resistance corresponds to IK02 class. These characteristics make the ENOLA 2.0 M a functional solution for use in various indoor areas, where technical quality and easy integration are prioritised.



Item no.	1011716
Socket	GU10
Number of sockets	1
IP Code	IP20
Impact resistance class	IK02
Assembly	Track
Assembly details	Pendant mounted,
Primary nominal voltage	220-240V ~ 50/60Hz
Safety class	II
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Color	white
Height	10.5 cm
Diameter	5.8 cm
Pendant length	200.0000 cm
Net weight	0.25 kg
Gross weight	0.34 kg
BIG WHITE Page	565

Recommended light bulbs

1005076	LED lightbulb QPAR51, GU10, 2700 K, white
1012469	LED PAR16 Smart, GU10, Tunable White, Zigbee

Accessories

1011749	ENOLA 2.0/BIMA 2.0 M, Decorative ring, Ø 54 mm, black
1011750	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, white
1011751	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, gold
1011752	ENOLA 2.0/BIMA 2.0 M, decorative ring, Ø 54 mm, copper