


STREET A MICRO 52 740 | LENS710

STREET A, MICRO 52 740 LENS710

The STREET A MICRO streetlight is a luminaire head designed for outdoor use. It is particularly suitable for illuminating streets and pathways. The luminaire provides a luminous flux of 5250 lumens and has a declared service life of 100,000 hours. The housing is made of aluminium and features a glass cover. With dimensions of 57.3 cm in length, 22 cm in width, and 13.1 cm in height, it is compactly constructed. The IP66 rating ensures protection against dust and powerful water jets, while the IK09 impact resistance class offers high durability against mechanical impacts.



Item no.	1011735
Number of different light outlets	1
Tilt range	35°
IP Code	IP66
Impact resistance class	IK09
Impact resistance	10 Joule
Primary nominal voltage	220-240V V ~ 50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Safety class	I
Safety class	I
Safety class	I
Wattage	35 W
Minimum ambient temperature	-40°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	20.0
Number of luminaires at LS C16A	33.0
Level of inrush current	24.88 A
Duration of inrush current	236 µs
Beam angle	160°
Color	gray
CRI	70
LXXBXX data	L80B50
Service life	100 000 h
Risk Group	1
Length	57.3 cm
Width	22 cm
Height	13.1 cm
Net weight	3.6 kg