


STREET A MICRO 52 730 | LENS906

STREET A, MICRO 52 730 LENS906

Luminaire head STREET A MICRO 52 730 LENS906, suitable for street lighting. The product is designed for outdoor use and offers a luminous flux of 5250 lumens. The housing is made of aluminium, with a glass cover. With dimensions of 57.3 cm length, 22 cm width, and 13.1 cm height, the luminaire is compactly designed. It features an IP66 rating, providing high protection against dust and water ingress, as well as an impact resistance class of IK09. The declared lifespan is 100,000 hours.



Item no.	1011739
Number of different light outlets	1
IP Code	IP66
Impact resistance class	IK09
Impact resistance	10 Joule
Primary nominal voltage	220-240V V ~ 50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	35 W
Minimum ambient temperature	-40°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	20.0
Number of luminaires at LS C16A	33.0
Level of inrush current	24.88 A
Duration of inrush current	236 µs
Beam angle	145°
Color	gray
CRI	70
LXXBXX data	L80B50
Service life	100 000 h
Risk Group	1
Length	57.3 cm
Width	22 cm
Height	13.1 cm
Net weight	3.6 kg
Gross weight	4.6 kg