


WL 149 | WL, PHASE

WL 149, WL, PHASE, surface-mounted wall luminaire, 3000 K, 10 W, black

The WL 149 is a surface-mounted wall light suitable for indoor lighting. It features a colour temperature of 3000 K and delivers a luminous flux of 600 lumens with a power consumption of 10 watts. The luminaire is equipped with PHASE-cut dimming, allowing flexible brightness adjustment. The housing is made of steel and glass, ensuring a robust construction. With dimensions of 24 cm width, 6 cm height, and 10 cm depth, the light is compactly designed. The IP20 rating makes it suitable for use in dry indoor environments. The WL 149 offers a declared lifespan of 50,000 hours and is designed for use in residential and work areas.



Light source

2014568	A C

Item no.	1011747
IP Code	IP20
Assembly	Surface
Assembly details	Wall,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	56.0
Number of luminaires at LS C16A	118.0
Level of inrush current	5 A
Duration of inrush current	300 µs
Color	black
CRI	90
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Width	24 cm
Height	6 cm
Depth	10
Net weight	1.11 kg
Gross weight	1.32 kg
BIG WHITE Page	347