
LOGS IN L | WL, DALI

LOGS IN L, Wall-Mounted Luminaire, DALI, 3000 K, 20 W, white

The LOGS IN L wall-mounted luminaire is designed for indoor use and is particularly suitable for illuminating walls in residential and commercial areas. It features a colour temperature of 3000 K and a power consumption of 20 W with a luminous flux of 2000 lumens. The luminaire is equipped with DALI 2 and touch dimming, allowing flexible light control. The housing is made of aluminium and steel and measures 30 cm in length, 10 cm in depth, and 7 cm in height. The IP20 protection rating guards against contact, and the IK02 rating ensures low impact resistance. The luminaire offers a long service life of up to 50,000 hours and is designed for easy wall mounting.



Light source

2336922	A G E

Item no.	1011866
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall,
Dimmable	true
Dimming technology	DALI 2Touch
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	20 W
Ambient temperature	63
Minimum ambient temperature	0°C
Maximum ambient temperature	35°C
Number of luminaires at LS B16A	21.0
Number of luminaires at LS C16A	34.0
Level of inrush current	45 A
Duration of inrush current	16 µs
Color	white
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Length	30 cm
Height	7 cm
Depth	10
Net weight	1.39 kg
Gross weight	1.6 kg
BIG WHITE Page	345