


LINIUS 150 | PD, PHASE, RECESSED

LINIUS 150, PD, PHASE, RECESSED, pendant luminaire, 2700 K, 40 W, 90°, black

The pendant luminaire from the LINIUS product line is designed for ceiling installation and is suitable for indoor use with an IP20 protection rating. It features a rectangular canopy shape with a round cut-out, and the housing is made of aluminium. With a length of 150 cm, a width of 0.76 cm, and a height of 7.9 cm, it offers a slim design. The luminaire delivers a luminous flux of 3350 lumens with a service life of 50,000 hours. Dimming is carried out via phase-cut control (trailing edge). The impact resistance is rated IK02. The pendant length is 200 cm, allowing for flexible mounting options. This technical specification makes the luminaire suitable for professional installations in offices, retail spaces, or public buildings.



Item no.	1011946
IP Code	IP20
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	64
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	1050
Safety class	II
Wattage	40 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	64.0
Number of luminaires at LS C16A	128.0
Level of inrush current	15 A
Duration of inrush current	10 µs
Beam angle	90°
Color	black
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	150 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.3 kg