


LINIUS 150 | PD, PHASE, RECESSED

LINIUS 150, PD, PHASE, RECESSED, pendant luminaire, 3000 K, 40 W, 90°, black

The pendant light LINIUS 150 is designed for ceiling installation and is suitable for indoor use. It offers a luminous flux of 3450 lumens with a colour temperature of 3000 K and a beam angle of 90°. The luminaire features phase-cut dimming, allowing for stepless brightness adjustment. The housing is made of aluminium and comes in a black finish. The rectangular canopy and the round cut-out enable flexible mounting. With a length of 150 cm, a width of 0.76 cm, and a height of 7.9 cm, the luminaire has compact dimensions. The suspension length is 200 cm. The IP20 protection rating and IK02 impact resistance ensure reliable operation in protected indoor areas. The declared service life is 50,000 hours.



Item no.	1011948
IP Code	IP20
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	64
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	1050
Safety class	II
Wattage	40 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	64.0
Number of luminaires at LS C16A	128.0
Level of inrush current	15 A
Duration of inrush current	10 µs
Beam angle	90°
Color	black
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	150 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.3 kg