


LINIUS 150 | PD, PHASE, RECESSED

LINIUS 150, PD, PHASE, RECESSED, pendant luminaire, 3000 K, 40 W, 90°, brass-colored

The LINIUS 150 pendant luminaire is designed for ceiling installation and is suitable for indoor use, for example in offices or retail spaces. It has a power rating of 40 watts and produces a light colour of 3000 Kelvin with a beam angle of 90 degrees, providing uniform and glare-free illumination. The housing is made of aluminium and finished in brass colour. The luminaire features a rectangular canopy shape and a round cut-out. With a length of 150 cm and a suspension length of 200 cm, it is suitable for larger rooms or areas with higher ceilings. Dimming is performed via PHASE-cut (Trailing Edge). Protection class IP20 and impact resistance according to IK02 ensure safe operation in protected indoor areas. The declared service life is 50,000 hours.



Item no.	1011949
IP Code	IP20
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	64
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	1050
Safety class	II
Wattage	40 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	64.0
Number of luminaires at LS C16A	128.0
Level of inrush current	15 A
Duration of inrush current	10 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	150 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.3 kg