


LINIUS 120 | PD, DALI RECESSED

LINIUS 120, PD, DALI, RECESSED, pendant luminaire, 2700 K, 34 W, 90°, brass-coloured

The pendant light LINIUS 120 is designed for ceiling installation and is particularly suitable for indoor use, such as in offices or meeting rooms. It provides a luminous flux of 3000 lumens with a colour temperature of 2700 K and a beam angle of 90°. The luminaire is equipped with DALI 2 dimming, allowing flexible light control. The housing is made of aluminium and finished in a brass colour. The luminaire measures 121 cm in length, 7.9 cm in height, and 0.76 cm in width. The canopy is rectangular, while the cut-out is round. The protection rating is IP20, and the mechanical impact resistance corresponds to IK02. The suspension length is 200 cm.



Item no.	1011955
IP Code	IP20
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	900
Safety class	II
Wattage	34 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	15.0
Number of luminaires at LS C16A	24.0
Level of inrush current	65 A
Duration of inrush current	200 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	121 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.06 kg