


LINIUS 120 | PD, DALI RECESSED

LINIUS 120, PD, DALI, RECESSED, pendant luminaire, 3000 K, 34 W, 90°, brass-coloured

The pendant luminaire LINIUS 120, PD, DALI is designed for ceiling installation and is suitable for indoor use, particularly in office and work areas. It offers a luminous flux of 3100 lumens at a colour temperature of 3000 K and a beam angle of 90°. The luminaire features a DALI-2 dimming function, allowing flexible light control. The housing is made of aluminium and finished in brass colour. The luminaire measures 121 cm in length, 0.76 cm in width, and 7.9 cm in height, with a maximum suspension length of 200 cm. It has an IP20 protection rating and an impact resistance class of IK02.



Item no.	1011957
IP Code	IP20
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	900
Safety class	II
Wattage	34 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	15.0
Number of luminaires at LS C16A	24.0
Level of inrush current	65 A
Duration of inrush current	200 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	121 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.06 kg