


LINIUS 150 | PD, DALI RECESSED

LINIUS 150, PD, DALI, RECESSED, pendant luminaire, 3000 K, 40 W, 90°, black

The LINIUS 150 pendant luminaire is designed for ceiling installation and is suitable for indoor use, for example in offices or meeting rooms. It provides a luminous flux of 3450 lumens with a colour temperature of 3000 Kelvin and a beam angle of 90 degrees. The luminaire is equipped with a DALI-2 dimming function, allowing flexible light control. The housing is made of aluminium and comes in a black finish. With a length of 150 cm and a pendant drop of 200 cm, it features a slim design measuring 7.9 cm in height and 0.76 cm in width. The luminaire has an IP20 protection rating and an IK02 impact resistance.



Item no.	1011964
IP Code	IP20
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	1050
Safety class	II
Wattage	40 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	15.0
Number of luminaires at LS C16A	24.0
Level of inrush current	65 A
Duration of inrush current	200 µs
Beam angle	90°
Color	black
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	150 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.36 kg