


LINIUS 150 | PD, DALI RECESSED

LINIUS 150, PD, DALI, RECESSED, pendant luminaire, 3000 K, 40 W, 90°, brass-coloured

The LINIUS 150 pendant light is designed for ceiling installation and is suitable for indoor use. It delivers a luminous flux of 3450 lumens at a colour temperature of 3000 K with a beam angle of 90°. The luminaire operates at 40 watts and features DALI-2 dimming for flexible light control. The housing is made of aluminium with a brass-coloured finish. The luminaire measures 150 cm in length, 7.9 cm in height, and 0.76 cm in width, with a suspension length of 200 cm. The rectangular canopy and round cut-out allow for easy installation. It has an IP20 protection rating and an impact resistance rating of IK02. The declared LED lifespan is 50,000 hours.



Item no.	1011965
IP Code	IP20
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	15
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	1050
Safety class	II
Wattage	40 W
Minimum ambient temperature	0°C
Maximum ambient temperature	45°C
Number of luminaires at LS B16A	15.0
Number of luminaires at LS C16A	24.0
Level of inrush current	65 A
Duration of inrush current	200 µs
Beam angle	90°
Color	brass
CRI	90
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	150 cm
Width	0.8 cm
Height	7.9 cm
Pendant length	200.0000 cm
Net weight	2.36 kg