


PL-BEAM PRO M | SP, DALI

PL-BEAM PRO M, SP, DALI, wall and ceiling surface-mounted luminaire, 2700 K, 26 W, 23°, anthracite

The LED spotlight PL-BEAM PRO M is designed for wall and ceiling mounting and is suitable for use in indoor and outdoor areas that require robust and high-performance lighting. With a luminous flux of 3350 lumens at 26 watts and a colour temperature of 2700 K, it produces warm white light with a beam angle of 23°. The housing is made of aluminium and features a glass cover. The spotlight has an IP66 rating and an impact resistance class of IK08, making it resistant to dust, water, and mechanical impacts. Dimming is carried out via the DALI-2 protocol, allowing flexible control options. With a height of 19.4 cm and a diameter of 16.2 cm, the device is compactly designed and suitable for a wide range of applications.



Item no.	1012119
Lamps included	No
IP Code	IP66
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Surface
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	30
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	37.0
Number of luminaires at LS C16A	62.0
Level of inrush current	24 A
Duration of inrush current	98 µs
Temperature at glass (light emission)	60
Beam angle	23°
Color	anthracite
CRI	80
LXXBXX data	L80B20
Service life	70 000 h
Risk Group	1
Height	19.4 cm
Diameter	16.2 cm
Net weight	1.95 kg

Accessories

1012132	PL-BEAM PRO M, SHADE, anthracite
1012134	PL-BEAM PRO M, HONEYCOMB LOUV-RE, black
1012135	PL-BEAM PRO S/M, POLE CLAMP, anthracite
234350	WALL BRACKET, for outdoor spotlights, 80 cm, black