


PL-BEAM PRO M | SP, DALI, ASYM

PL-BEAM PRO M, SP, DALI, ASYMMETRIC, wall and ceiling surface-mounted luminaire, 2700 K, 26 W, 25°, anthracite

The LED spotlight PL-BEAM PRO M is designed for wall and ceiling mounting and is suitable for use in indoor and outdoor areas requiring robust and powerful lighting. With a colour temperature of 2700 K, it produces warm white light and offers a luminous flux of 3300 lumens at a power consumption of 26 watts. The asymmetrical light distribution with a beam angle of 25° enables targeted illumination. The housing is made of aluminium and features a glass cover. The luminaire has an IP66 protection rating and an IK08 impact resistance class, making it resistant to dust, water jets, and mechanical impacts. Dimming is carried out via DALI 2, allowing flexible light control. With a height of 19.4 cm and a diameter of 16.2 cm, the luminaire is compact and functionally designed.



Item no.	1012123
Lamps included	No
IP Code	IP66
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Surface
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	30
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	37.0
Number of luminaires at LS C16A	62.0
Level of inrush current	24 A
Duration of inrush current	98 µs
Temperature at glass (light emission)	60
Beam angle	25°
Color	anthracite
CRI	80
LXXBXX data	L80B20
Service life	70 000 h
Risk Group	1
Height	19.4 cm
Diameter	16.2 cm
Net weight	1.95 kg

Accessories

1012132	PL-BEAM PRO M, SHADE, anthracite
1012134	PL-BEAM PRO M, HONEYCOMB LOUV-RE, black
1012135	PL-BEAM PRO S/M, POLE CLAMP, anthracite
234350	WALL BRACKET, for outdoor spotlights, 80 cm, black