


PL-BEAM PRO M | SP, DALI

PL-BEAM PRO M, SP, DALI, wall and ceiling surface-mounted luminaire, 3000 K, 26 W, 64°, anthracite

The LED spotlight PL-BEAM PRO M is suitable for wall and ceiling mounting in indoor and outdoor areas that require robust and high-performance lighting. With a luminous flux of 3300 lumens at 26 watts and a colour temperature of 3000 K, the device provides targeted illumination with a beam angle of 64°. The housing is made of aluminium and is equipped with a glass cover. The luminaire is dimmable via DALI 2 technology and features an IP66 protection rating as well as IK08 impact resistance, protecting it against dust, jet water, and mechanical impacts. The compact dimensions of 16.2 cm diameter and 19.4 cm height allow flexible installation in various environments. The declared service life is 70,000 hours.



Item no.	1012130
IP Code	IP66
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Surface
Dimmable	true
Dimming technology	DALI 2
Number of through-wires	30
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	37.0
Number of luminaires at LS C16A	62.0
Level of inrush current	24 A
Duration of inrush current	98 µs
Temperature at glass (light emission)	60
Beam angle	64°
Color	anthracite
CRI	80
LXXBXX data	L80B20
Service life	70 000 h
Risk Group	1
Height	19.4 cm
Diameter	16.2 cm
Net weight	1.95 kg
Gross weight	2.43 kg

Accessories

1012132	PL-BEAM PRO M, SHADE, anthracite
1012134	PL-BEAM PRO M, HONEYCOMB LOUV-RE, black
1012135	PL-BEAM PRO S/M, POLE CLAMP, anthracite
234350	WALL BRACKET, for outdoor spotlights, 80 cm, black