


ALEGRIA | WL, TRIAC

ALEGRIA, WL, TRIAC, surface-mounted wall luminaire, 2200 K / 2700 K, 9 W, anthracite

The ALEGRIA surface-mounted wall light is suitable for use in indoor and outdoor areas where a robust and protecti-on-tested lighting solution is required. It features a colour temperature range from 2200 K to 2700 K and a power consumption of 9 watts with a luminous flux of 500 to 550 lumens. The housing is made of aluminium and polycar-bonate, ensuring a durable construction. With dimensions of approximately 21 cm width, 20.9 cm height, and 6 cm depth, the luminaire can be mounted space-efficiently on walls. The IP65 rating provides reliable protection against dust and jet water, while the IK08 impact resistance class guarantees high mechanical durability. The luminaire is designed for PHASE cut-on and cut-off dimming, allowing flexible control options.



Item no.	1012140
Lamps included	No
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Surface
Assembly details	Wall,
Dimmable	true
Dimming technology	Leading edgetrailing edge
Number of through-wires	50
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	160 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	50°C
Number of luminaires at LS B16A	256.0
Number of luminaires at LS C16A	256.0
Level of inrush current	6.72 A
Duration of inrush current	96 µs
Temperature at glass (light emission)	60
Beam angle	6°
Color	anthracite
CRI	80
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	1
Width	21 cm