


GLENOS® 2.0 | PD, 1.2M, DALI, UGR19

GLENOS® 2.0, PD, 1.2M, DALI, UGR19, Pendant luminaire, Pendant length: 200 cm, 4000 K, 38 W, 80°, black

The GLENOS® 2.0 pendant luminaire is designed for indoor use and is particularly suitable for office and work areas where glare-free lighting is required. With a power consumption of 38 watts, it produces a luminous flux of 5800 lumens at a colour temperature of 4000 K, providing neutral, daylight-like illumination. The luminaire features a rectangular canopy and a suspension length of 200 cm, allowing flexible installation at various ceiling heights. The housing is made of aluminium and is designed with a UGR value of 19 for low glare. The light distribution has a beam angle of 80 degrees. The luminaire is equipped with DALI-2 dimming and touch control and has an IP20 protection rating. Its dimensions are 120 cm in length, 4.8 cm in width, and 7 cm in height.



Item no.	1012157
Number of different light outlets	2
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	25
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	1050 mA
Safety class	I
Wattage	38 W
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	29.0
Number of luminaires at LS C16A	48.0
Level of inrush current	15.88 A
Duration of inrush current	240 µs
Beam angle	80°
Color	black
CRI	80
UGR ≤	19
LXXBXX data	L80B20
Service life	100 000 h
Length	120 cm
Width	4.8 cm
Height	7 cm
Pendant length	200.0000 cm
Net weight	3.8 kg
Gross weight	5.4 kg