


# GLENOS® 2.0 | PD, 1.5M, DALI, UGR19

**GLENOS® 2.0, PD, 1.5M, DALI, UGR19, Pendant luminaire, Pendant length: 200 cm, 3000 K, 46 W, 80°, white**

The GLENOS® 2.0 pendant luminaire is designed for indoor use and is particularly suitable for office and work areas. It has a length of 150 cm and a suspension length of 200 cm, allowing flexible installation at various ceiling heights. The luminaire features DALI-2 dimming and touch control, enabling precise light adjustment. With a power consumption of 46 watts, it produces a luminous flux of 7500 lumens at a colour temperature of 3000 Kelvin and a beam angle of 80 degrees. The housing is made of aluminium and finished in white. The luminaire is rated IP20 and equipped with UGR19 glare limitation, ensuring comfortable and efficient lighting. Its compact design, with a height of 7 cm and a width of 4.8 cm, supports discreet integration into modern room concepts.




| | |
|---|---|
| **Item no.** | 1012158 |
| **Number of different light outlets** | 2 |
| **IP Code** | IP20 |
| **Assembly** | Surface |
| **Assembly details** | Ceiling suspended, |
| **Dimmable** | true |
| **Dimming technology** | DALI 2Touch |
| **Number of through-wires** | 20 |
| **Primary nominal voltage** | 200-240V ~ 0/50/60Hz |
| **Secondary power / voltage** | 1250 mA |
| **Safety class** | I |
| **Wattage** | 46 W |
| **Maximum ambient temperature** | 40°C |
| **Number of luminaires at LS B16A** | 20.0 |
| **Number of luminaires at LS C16A** | 33.0 |
| **Level of inrush current** | 19.5 A |
| **Duration of inrush current** | 272 µs |
| **Beam angle** | 80° |
| **Color** | white |
| **CRI** | 80 |
| **UGR ≤** | 19 |
| **LXXBXX data** | L80B20 |
| **Service life** | 100 000 h |
| **Length** | 150 cm |
| **Width** | 4.8 cm |
| **Height** | 7 cm |
| **Pendant length** | 200.0000 cm |
| **Net weight** | 4.3 kg |
| **Gross weight** | 5.8 kg |