


GLENOS® 2.0 | PD, 1.5M, DALI, UGR19

GLENOS® 2.0, PD, 1.5M, DALI, UGR19, Pendant luminaire, Pendant length: 200 cm, 4000 K, 46 W, 80°, black

The GLENOS® 2.0 pendant luminaire is designed for indoor use and is particularly suitable for offices or work areas where glare-free lighting is required. With a length of 150 cm and a suspension length of 200 cm, it offers flexible installation options. The housing is made of aluminium and features a rectangular canopy. The luminaire is equipped with DALI 2 and touch dimming functions, allowing precise control of light intensity. It delivers a luminous flux of 7200 lumens at 46 watts and a colour temperature of 4000 Kelvin, providing neutral, daylight-like illumination. The beam angle is 80°, and the UGR value of 19 ensures low glare. The IP20 protection rating is designed for use in dry indoor environments.



Item no.	1012161
Number of different light outlets	2
IP Code	IP20
Assembly	Surface
Assembly details	Ceiling suspended,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	20
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	1250 mA
Safety class	I
Wattage	46 W
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	20.0
Number of luminaires at LS C16A	33.0
Level of inrush current	19.5 A
Duration of inrush current	272 µs
Beam angle	80°
Color	black
CRI	80
UGR ≤	19
LXXBXX data	L80B20
Service life	100 000 h
Length	150 cm
Width	4.8 cm
Height	7 cm
Pendant length	200.0000 cm
Net weight	4.3 kg
Gross weight	5.8 kg