
GLENOS® 2.0 | WL, 1.5M, DALI, UGR22

GLENOS® 2.0, WL, Surface-mounted wall luminaire, 4000 K, 20 W, 80°, white

The GLENOS® 2.0 surface-mounted wall luminaire is designed for installation on walls in indoor areas. It offers a luminous flux of 2950 lumens at a colour temperature of 4000 K and a beam angle of 80°. The housing is made of aluminium and measures 150 cm in length, 7 cm in height, and 4.8 cm in depth. The luminaire is equipped with DALI 2 and touch dimming functions, allowing for flexible light control. With an IP20 protection rating, it is suitable for use in protected indoor environments. The luminaire features a declared lifetime of 100,000 hours and includes glare control (UGR22).



Item no.	1012168
Number of different light outlets	1
IP Code	IP20
Assembly	Surface
Assembly details	Wall,
Dimmable	true
Dimming technology	DALI 2Touch
Number of through-wires	40
Primary nominal voltage	200-240V ~ 0/50/60Hz
Secondary power / voltage	550 mA
Safety class	I
Wattage	20 W
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	29.0
Number of luminaires at LS C16A	48.0
Level of inrush current	15.88 A
Duration of inrush current	240 µs
Beam angle	80°
Color	white
CRI	80
UGR ≤	22
LXXBXX data	L80B20
Service life	100 000 h
Length	150 cm
Height	7 cm
Depth	4.8
Net weight	4.3 kg
Gross weight	5.8 kg
BIG WHITE Page	320