


# GLENOS® 2.0 | WL, 1.5M, DALI, UGR22

**GLENOS® 2.0, WL, Surface-mounted wall luminaire, 4000 K, 20 W, 80°, black**

The GLENOS® 2.0 is a surface-mounted wall luminaire suitable for indoor use. It features a colour temperature of 4000 K and a power consumption of 20 W with a beam angle of 80°. The housing is made of aluminium and measures 150 cm in length, 7 cm in height, and 4.8 cm in depth. The luminaire is equipped with DALI 2 and touch dimming technology and offers glare control with a UGR value of 22. The protection rating is IP20. The luminaire is designed for a long service life of up to 100,000 hours.




| | |
|---|---|
| Item no. | 1012169 |
| Number of different light outlets | 1 |
| IP Code | IP20 |
| Assembly | Surface |
| Assembly details | Wall, |
| Dimmable | true |
| Dimming technology | DALI 2Touch |
| Number of through-wires | 40 |
| Primary nominal voltage | 200-240V ~ 0/50/60Hz |
| Secondary power / voltage | 550 mA |
| Safety class | I |
| Wattage | 20 W |
| Maximum ambient temperature | 40°C |
| Number of luminaires at LS B16A | 29.0 |
| Number of luminaires at LS C16A | 48.0 |
| Level of inrush current | 15.88 A |
| Duration of inrush current | 240 µs |
| Beam angle | 80° |
| Color | black |
| CRI | 80 |
| UGR ≤ | 22 |
| LXXBXX data | L80B20 |
| Service life | 100 000 h |
| Length | 150 cm |
| Height | 7 cm |
| Depth | 4.8 |
| Net weight | 4.3 kg |
| Gross weight | 5.8 kg |
| BIG WHITE Page | 320 |