


# GRIP! S MINI | 48V, DALI, SHORT, STANDARD TRACK, Ø 3.0CM

**GRIP! S MINI, 48V Spot, DALI, SHORT, Standard Track, 2700 K, 4.2 W, 29°, black / gold-coloured**

The GRIP! S MINI is a 48V spot designed for mounting on ceiling or wall track systems, making it particularly suitable for indoor use. With a colour temperature of 2700 K and a beam angle of 29°, it provides targeted light distribution with a power consumption of 4.2 W and a luminous flux of 260 lumens. The housing is made of aluminium and measures 17 cm in length, 3 cm in width, and 4 cm in height. The luminaire features a DALI 2 dimming function, allowing for flexible control. The protection rating is IP20, and impact resistance is classified as IK02. The declared lifetime is 50,000 hours.




## Light source

| | |
|---|---|
| 2093820 | A G D |

| | |
|---|---|
| Item no. | 1012172 |
| Number of different light outlets | 1 |
| IP Code | IP20 |
| Impact resistance class | IK02 |
| Impact resistance | 0.2 Joule |
| Assembly | Track |
| Assembly details | Ceiling,Wall, |
| Dimmable | true |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 48V DC |
| Secondary power / voltage | 100 mA |
| Safety class | III |
| Wattage | 4 W |
| Minimum ambient temperature | 0°C |
| Maximum ambient temperature | 30°C |
| Beam angle | 29° |
| Color | black/gold |
| CRI | 90 |
| UGR ≤ | 25 |
| LXXBXX data | L80B10 |
| Service life | 50 000 h |
| Risk Group | 1 |
| Length | 17 cm |
| Width | 3 cm |
| Height | 4 cm |
| Net weight | 0.09 kg |
| Gross weight | 0.14 kg |
| BIG WHITE Page | 463 |

## Accessories

| | |
|---|---|
| **1011829** | GRIP! S, decorative ring, white |
| **1011830** | GRIP! S, decorative ring, black |
| **1011831** | GRIP! S, decorative ring, nickel |
| **1011832** | GRIP! S, decorative ring, gold |
| **1011837** | GRIP! S, HONEYCOMB |