


GRIP! S | WL, PHASE, UP/DOWN, Ø 3,0CM

GRIP! S, WL, PHASE, UP/DOWN, wall-mounted luminaire, 2700 K, 12 W, 29°, white / black

The GRIP! S is a surface-mounted wall luminaire designed for indoor use. It features phase-cut dimming and delivers a light output of 740 lumens at 12 watts with a colour temperature of 2700 Kelvin. The beam angle is 29 degrees, directing the light specifically upwards and downwards. The housing is made of aluminium and measures 30 cm in height, 3 cm in width, and 6.2 cm in depth. The luminaire has an IP20 protection rating against foreign objects and an impact resistance class of IK02. It is suitable for applications where discreet, directed wall lighting is required.



Light source

2093820	A to G: D

Item no.	1012174
Number of different light outlets	2
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	300 mA
Safety class	I
Wattage	12 W
Minimum ambient temperature	0°C
Maximum ambient temperature	35°C
Number of luminaires at LS B16A	120.0
Number of luminaires at LS C16A	192.0
Level of inrush current	8 A
Duration of inrush current	40 µs
Beam angle	29°
Color	white/black
CRI	90
UGR ≤	25
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Width	3 cm
Height	30 cm
Depth	6.2

Accessories

1011829	GRIP! S, decorative ring, white
1011830	GRIP! S, decorative ring, black
1011831	GRIP! S, decorative ring, nickel
1011832	GRIP! S, decorative ring, gold
1011837	GRIP! S, HONEYCOMB