


GRIP! S | WL, PHASE, UP/DOWN, Ø 3,0CM

GRIP! S, WL, PHASE, UP/DOWN, wall-mounted luminaire, 2700 K, 12 W, 29°, bronze / black

This surface-mounted wall light from the GRIP! product line is designed for indoor use and provides a luminous flux of 740 lumens with a lifespan of 50,000 hours. The housing is made of aluminium and measures 30 cm in height, 3 cm in width, and 6.2 cm in depth. The luminaire features PHASE-cut dimming and is rated IP20 for protection as well as IK02 for impact resistance. Its compact design makes it suitable for wall mounting and offers an efficient and durable lighting solution.



Light source

2093820	A to G D

Item no.	1012176
Number of different light outlets	2
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall,
Dimmable	true
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	300 mA
Safety class	I
Wattage	12 W
Minimum ambient temperature	0°C
Maximum ambient temperature	35°C
Number of luminaires at LS B16A	120.0
Number of luminaires at LS C16A	192.0
Level of inrush current	8 A
Duration of inrush current	40 µs
Beam angle	29°
Color	bronze/black
CRI	90
UGR ≤	25
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Width	3 cm
Height	30 cm
Depth	6.2

Accessories

1011829	GRIP! S, decorative ring, white
1011830	GRIP! S, decorative ring, black
1011831	GRIP! S, decorative ring, nickel
1011832	GRIP! S, decorative ring, gold
1011837	GRIP! S, HONEYCOMB