


LIPSY® 2.0 40 | CW, DRUM

LIPSY® 2.0 40, CW, DRUM, Wall and Ceiling Surface-Mounted Luminaire, 3000 K / 4000 K, 9/18 W, 120°, white / milky

The LIPSY® 2.0 40 is a surface-mounted wall and ceiling luminaire designed for indoor use. It offers a selectable colour temperature of 3000 K or 4000 K and is available with a luminous power of 9 or 18 watts. The beam angle is 120°, ensuring uniform illumination. The housing is made of steel, while the diffuser is manufactured from PMMA. The luminaire has a diameter of 40 cm and a height of 9.7 cm. It is protected against splashing water with an IP44 rating and has an impact resistance class of IK02. The LIPSY® 2.0 40 is therefore suitable for a wide range of applications requiring a robust and functional lighting solution.



Item no.	1012187
IP Code	IP44
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,Wall,
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	75/105/150mA
Safety class	I
Wattage	9 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	133.0
Number of luminaires at LS C16A	133.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	120°
Color	white/milky
CRI	80
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	9.7 cm
Diameter	40 cm
Net weight	0.75 kg
Gross weight	1.4 kg
BIG WHITE Page	393