
SENSER 2.0 24 | RL, ROUND, PHASE

SENSER 2.0 24, RL, round, PHASE, recessed ceiling luminaire, 3000 K / 4000 K, 90°, 18 W, white

The recessed ceiling light from the SENSER product line is designed for installation in ceilings and is suitable for indoor areas with an IP20 protection rating. It features a round design with a diameter of 22.5 cm and a slim height of 2.4 cm. The housing is made of aluminium, while the diffuser is made of polycarbonate. The luminaire delivers a light output of 1800 to 1900 lumens with a lifespan of 50,000 hours. Dimming is achieved via trailing edge phase control. With an IK02 impact protection rating, the luminaire is protected against light mechanical impacts and is suitable for use in areas without high humidity exposure.



Item no.	1012202
Lamps included	No
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	60
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	18 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	145.0
Number of luminaires at LS C16A	145.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	90°
Color	white
CRI	90
UGR ≤	25
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Height	2.4 cm
Diameter	22.5 cm