
SENSER 2.0 24 | RL, SQUARE, PHASE

SENSER 2.0 24, RL, square, PHASE, recessed ceiling luminaire, 3000 K / 4000 K, 20 W, 90°, white

The SENSER 2.0 24 is a square recessed ceiling luminaire suitable for indoor use. It features phase-cut dimming and is available in colour temperatures of 3000 K and 4000 K. With a power consumption of 20 watts, it produces a luminous flux of approximately 1900 to 2000 lumens at a beam angle of 90°. The housing is made of aluminium and polycarbonate, and the luminaire has a slim design measuring 22.5 x 22.5 cm with a height of 2.4 cm. With an IP20 rating and IK02 impact resistance, it is intended for use in protected indoor areas. The luminaire is designed for recessed ceiling installation and offers a long-lasting lighting solution with a lifespan of 50,000 hours.



Item no.	1012203
Lamps included	No
IP Code	IP20
Impact resistance class	IK02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling,
Dimmable	true
Dimming technology	trailing edge
Number of through-wires	60
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	20 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	145.0
Number of luminaires at LS C16A	145.0
Level of inrush current	5 A
Duration of inrush current	100 µs
Beam angle	90°
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L80B10
Service life	50 000 h
Risk Group	1
Length	22.5 cm
Width	22.5 cm