

LEDSTRIP SMD TW | S

LED STRIP SMD TW, IP67, S, 2700 K / 6500 K, L: 500 cm, 4400/4750 lm

The LED strip is suitable for use in both indoor and outdoor areas, as it is protected against dust and water ingress with an IP67 rating. With a length of 500 cm and a width of 1.2 cm, it offers flexible design options for linear lighting applications. The colour temperature is adjustable between 2700 K and 6500 K, allowing for different atmospheres. The luminous flux ranges from 4400 to 4750 lumens, ensuring bright illumination. The flat design with a height of 0.5 cm facilitates installation on various surfaces. The LED strip has a lifespan of 50,000 hours, indicating a long service life. The LED strip is particularly suitable for architects, planners, and electrical specialists who require a flexible and robust lighting solution.

Accessories

1012603	LED STRIP CONNECTOR IP SEALING SET, 10 MM

Item no.	1012278
Number of different light outlets	1
IP Code	IP67
Assembly	Surface
Assembly details	Ceiling,Wall,
LED distance	0,9 cm
Safety class	III
Safety class	III
Safety class	III
Safety class	III
Ambient temperature	59
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Beam angle	120°
CRI	90
Binning	5.0000
LXXBXX data	L80B20
Service life	50 000 h
Risk Group	0
Length	500 cm
Width	1.2 cm
Height	0.5 cm
Net weight	0.29 kg
Gross weight	0.4 kg
BIG WHITE Page	621