

# OUT 65

**outdoor recessed ceiling light, LED, 3000K, square, white, 38°, 12W, incl. driver**

The innovative OUT 65 recessed ceiling light captivates with its exceptional looks. Rated IP65 it can be used outdoors or in damp areas. It is available in black, white, silver-grey or titanium, and in round or square form. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 114471 |
| **IP Code** | IP 20 / IP 65 |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Dimmable** | Yes |
| **Dimming technology** | Leading edge,trailing edge |
| **Primary nominal voltage** | 220-240V ~50/60Hz |
| **Secondary power / voltage** | 500 mA |
| **Safety class** | II |
| **Wattage** | 11 W |
| **Level of inrush current** | 2 A |
| **Duration of inrush current** | 40 µs |
| **Stroboscopic effect (SVM)** | 0.02 |
| **Lumen** | 640 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 38 ° |
| **Color** | white |
| **CRI** | 80 |
| **LXXBXX data** | L70B50 |
| **Service life** | 40000 h |
| **Length** | 8.2 cm |
| **Width** | 8.2 cm |

| | |
|---|---|
| 916451 |  |

| | |
|---|---|
| **Height** | 6 cm |
| **Net weight** | 0.349 kg |
| **Gross weight** | 0.416 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 6 cm |
| **Installation diameter** | 7 cm |