


H-POL

pathway and floor stand, single-headed, LED, 3000 K, anthracite, L/W/H 16.5/16.5/66 cm

The H-POL SINGEL indirect radiating floor stand is made of aluminium and plastic. With protection class IP55, it is suitable for outdoor use. Thanks to the 8 W LED, the luminaire is ideal for use as a pathway light. The product is designed for floor installation and is through-wireable. A large mounting pot is available for optimum mounting in the earth. Thanks to the built-in LED driver, it can be connected directly to the 230V mains supply.



TECHNICAL DATA

Item no.	232165
IP Code	IP65
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Number of through-wires	18
Primary nominal voltage	100-277V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	18 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	17 A
Duration of inrush current	35 µs
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	anthracite
CRI	80
Service life	30000 h
Risk Group	0
Length	16.5 cm
Width	16.5 cm

916393	

Accessories

232195	MOUNTING POT , for H-POL pathway and floor stand, anthracite

Height	66 cm
Net weight	2.342 kg
Gross weight	3.14 kg
Shape of cut-out	square
Installation length	11.8 cm
Installation width	11.8 cm
Installation depth	10 cm
BIG WHITE Page	788