


H-POL

pathway and floor stand, double-headed, LED, 3000 K, anthracite, L/W/H 16.5/16.5/66 cm

The H-POL DOUBLE indirect radiating floor stand is made of aluminium and plastic. With protection class IP55, it is suitable for outdoor use. Thanks to the two 8 W LEDs, the luminaire is ideal for use as a pathway light. The product is designed for floor installation and is through-wireable. A large mounting pot is available for optimum mounting in the earth. Thanks to the built-in LED driver, it can be connected directly to the 230V mains supply.



TECHNICAL DATA

Item no.	232185
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Number of through-wires	9
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	1000 mA
Safety class	I
Wattage	35 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	10 A
Duration of inrush current	300 µs
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	anthracite
CRI	80
Service life	30000 h
Risk Group	0
Length	16.5 cm

916393	

Accessories

232195	MOUNTING POT , for H-POL pathway and floor stand, anthracite

Width	16.5 cm
Height	66 cm
Net weight	2.556 kg
Gross weight	3.417 kg
Shape of cut-out	square
Installation length	11.8 cm
Installation width	11.8 cm
Installation depth	10 cm
BIG WHITE Page	789