




## KALU

wall and ceiling light, single-headed, LED, 3000K, white/black, 60°

As one would expect, the LED extension of the popular KALU series guarantees the utterly free adjustment of lamp heads. Fitted with dimmable, high output LEDs, the KALU series has just become even more efficient and versatile! Available in matt black or black and white, KALU wall and ceiling light is supplied ready for direct connection to 230V mains supply.



## TECHNICAL DATA

Item no.	1000128
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	17 W
Level of inrush current	10 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.02
Lumen	1000 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	40000 h



## Light Source

916610	
--------	---

Light distribution	rotational symmetric
Light outlet	direct
Length	13 cm
Width	8.9 cm
Height	16 cm
Net weight	0.812 kg
Gross weight	0.947 kg
BIG WHITE Page	403

