




PANEL 60 round

LED Indoor surface-mounted ceiling light, silver-grey, 4000K

The LED PANEL 60 comes with several different light and housing colours, and provides a modern and space-saving solution for an efficient type of basic lighting. The high degree of luminous flux provides a pleasant, homogeneous and glare-free lighting feeling. The electrical connection is made directly to the 230V mains voltage supply. This luminaire contains built-in LED lamps.



TECHNICAL DATA

| | |
|-----------------------------------|-------------------|
| Item no. | 1000786 |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Number of through-wires | 40 |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 1000 mA |
| Safety class | I |
| Wattage | 42 W |
| Level of inrush current | 9 A |
| Duration of inrush current | 50 µs |
| Stroboscopic effect (SVM) | 0.04 |
| Lumen | 3350 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 110 ° |
| Color | grey |
| CRI | 80 |
| UGR ≤ | 22 |
| LXXBXX data | L70B50 |
| Service life | 30000 h |



Light Source

| | |
|--------|---|
| 916481 |  |
|--------|---|

| | |
|--------------------|----------------------|
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Height | 5.5 cm |
| Diameter | 60 cm |
| Net weight | 4.525 kg |
| Gross weight | 5.825 kg |
| BIG WHITE Page | 274 |

