




## Q-LINE PD

**LED Indoor pendant light, 2m, BAP, black, 4000K**

The Q-LINE ceiling light is optionally available with a white, black, or silver-grey luminaire housing. It is also available with a pure white or warm white LED, and different dimensions. Its high luminance and UGR value of less than 10 make the Q-Line luminaire suitable for workstations. Thanks to the TRIAC dimmable LED driver, the luminaire can be directly connected to the 230 Volt mains voltage supply.



## TECHNICAL DATA

Item no.	1000936
Number of different light outlets	1
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	900 mA
Safety class	I
Wattage	93 W
Level of inrush current	30 A
Duration of inrush current	40 $\mu$ s
Stroboscopic effect (SVM)	0.08
Lumen	4600 lm
Colour temperature	4000 Kelvin
Beam angle	30 °
Color	black
CRI	90
UGR $\leq$	10
LXXBXX data	L70B50
Service life	25000 h



## Light Source

916460 

Light distribution	axis symmetric
Light outlet	direct
Length	200 cm
Width	6 cm
Height	6 cm
Pendant length	150 cm
Net weight	4.502 kg
Gross weight	5.342 kg
BIG WHITE Page	293

