






## **DOLIX OUT QPAR51**

## round, white

The DOLIX OUT high-voltage recessed ceiling ring is made from aluminium and has glass protection against splashing water. Thanks to its IP65 rating, it is suitable for use outdoors and in wet rooms. The integrated GU10 high-voltage fitting means the DOLIX OUT recessed ceiling ring is ready for immediate connection to the 230V mains voltage.



## **TECHNICAL DATA**

Item no.	1001165
Socket	GU10
Number of sockets	1
IP Code	IP 65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Safety class	II
Wattage	50 W
Color	white
Light outlet	direct
Height	11 cm
Diameter	8.2 cm
Net weight	0.184 kg
Gross weight	0.217 kg
Shape of cut-out	round
Installation depth	11 cm
Installation diameter	6.8 cm
BIG WHITE Page	235





## Recommended lamp

1005273	QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36°
1005079	LED lightbulb QPAR51 , GU10, 3000K, white
1005076	LED lightbulb QPAR51 , GU10, 2700K, white
1005082	LED lightbulb QPAR51 , GU10, 4000K, white