




## AKALO 83

DL, indoor recessed ceiling light, 3000K 4200K 5700K adjustable, white

The AKALO luminaire is a recessed ceiling light for universal use indoors. The light temperature is switchable in all versions. The electrical connection is made directly to the 230V mains supply.



## TECHNICAL DATA

Item no.	1001264
Number of different light outlets	1
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	120 mA
Safety class	II
Wattage	9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	5 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0.01
Lumen	800/880/850 lm
Colour temperature	3000/4000/5700 Kelvin
Beam angle	90 °
Color	white
CRI	80



## Light Source

916471 

UGR $\leq$	28
LXXBXX data	L70B50
Service life	30000 h
Height	6.5 cm
Diameter	11 cm
Net weight	0.186 kg
Gross weight	0.243 kg
Shape of cut-out	round
Installation depth	7 cm
Installation diameter	9.2 cm
BIG WHITE Page	237