




Q-LINE DALI SINGLE LED

pendant, dimmable, 1500mm, black



The Q-LINE DALI wall light is available with a choice of a white, black, or silver-grey luminaire housing. A diffuser made of acrylic glass found underneath provides glare-free lighting properties. The integrated warm-white LEDs give an output of 3200 lm. Thanks to the DALI dimmable LED driver, the luminaire can be directly connected to the 230V mains supply.



TECHNICAL DATA

| | |
|---------------------------------------|-------------------|
| Item no. | 1001309 |
| Number of different light outlets | 1 |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI 2 |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 47 W |
| Rated standby power | 0.16 W |
| Number of luminaires at LS B16A | 14 |
| Number of luminaires at LS C16A | 23 |
| Level of inrush current | 40 A |
| Duration of inrush current | 178 µs |
| Temperature at glass (light emission) | 45 °C |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 3700 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 120 ° |
| Color | black |

Light Source

| | |
|--------|---|
| 916631 |  |
| 916371 |  |

| | |
|--------------------|----------------|
| CRI | 80 |
| UGR \leq | 28 |
| LXXBXX data | L70B50 |
| Service life | 30000 h |
| Light distribution | axis symmetric |
| Light outlet | direct |
| Length | 142 cm |
| Width | 6 cm |
| Height | 6 cm |
| Pendant length | 200 cm |
| Net weight | 3.525 kg |
| Gross weight | 4.179 kg |
| BIG WHITE Page | 293 |