




GLENOS

professional pendant, LED, 3000K, black, 1 m, 43W

The GLENOS pendant with a high-performance LED strip gives you a powerful, top-class LED lighting. The pendants are available in several lengths and colour variants and are fitted with a 2.50 m connection lead, which can be shortened individually. The GLENOS pendant is ready to connect to the 230 V mains supply thanks to the dimmable LED driver.



TECHNICAL DATA

Item no.	1001400
Number of different light outlets	1
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	1000 mA
Safety class	I
Wattage	43 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Level of inrush current	30 A
Duration of inrush current	300 µs
Stroboscopic effect (SVM)	0
Lumen	2850 lm
Colour temperature	3000 Kelvin
Color	black
CRI	80
UGR ≤	28
LXXBXX data	L70B50
Service life	35000 h
Light distribution	axis symmetric



Light Source

916482	
--------	--

Light outlet	direct
Length	105 cm
Width	5 cm
Height	7 cm
Pendant length	200 cm
Net weight	2.411 kg
Gross weight	3.031 kg
BIG WHITE Page	291