


TEC KALU double white/-black 24° 3000K

incl. 3-circuit adapter

The futuristic 240V TEC KALU with an appropriate adapter for the 3-circuit 240V track system has individually rotating and swivelling lamp heads with warm-white and dimmable premium LEDs. The built-in LED driver is located within the main structure. TEC KALU is supplied ready for direct connection to the 230V mains voltage supply.



TECHNICAL DATA

| | |
|-----------------------------|-------------------------|
| Item no. | 1001428 |
| Rotating or tilting | rotary Bar and tiltable |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Track Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 31 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Rated standby power | 0.5 W |
| Stroboscopic effect (SVM) | 0.03 |
| Lumen | 1900 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 24 ° |
| Color | white |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 40000 h |



Light Source

916610 

| | |
|--------------------|----------------------|
| Light distribution | rotational symmetric |
| Light outlet | direct |
| Length | 29.5 cm |
| Width | 17 cm |
| Height | 15.5 cm |
| Net weight | 1.686 kg |
| Gross weight | 2.144 kg |

