




TEC KALU CW

LED Indoor surface-mounted wall and ceiling light double, white/black 24° 3000K

This futuristic 240V wall and ceiling light TEC KALU has individually rotating and swivelling lamp heads, equipped with warm white and dimmable Premium LEDs. The built-in LED driver is located within the main structure. An optionally available suspension allows pendulum mode. TEC KALU is supplied ready for direct connection to the 230V mains voltage supply.



TECHNICAL DATA

Item no.	1001432
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	31 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Rated standby power	0.5 W
Stroboscopic effect (SVM)	0.03
Lumen	1900 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	40000 h

Light Source

916610	
--------	---

Accessories

1001436	TEC KALU suspension set , white
1001435	TEC KALU suspension set , black

Light distribution	rotational symmetric
Light outlet	direct
Length	29.5 cm
Width	17 cm
Height	15.3 cm
Net weight	1.813 kg
Gross weight	2.276 kg