




## MEDO 40 CW AMBIENT

LED Inddoorsurface-mounted wall and ceiling light, TRI-AC, black, 3000/4000K

The high quality MEDO AMBIENT supplements the MEDO series, and impresses with its well thought-out new features: Thanks to its homogeneous, indirect upwards light emission, it generates a decorative AMBIENT effect. A practical switch that provides flexibility, and with the MEDO AMBIENT variant is easy to switch between 3000K and 4000K. The MEDO AMBIENT also excels during installation: The base plate is screwed to the wall or the ceiling, then the body is simply attached to the socket using three clips and can be removed in the same way, of course. The ceiling light can be converted into a pendant using a suspension kit, and is therefore also ideal for rooms with high ceilings. The built-in LED driver makes direct connection to a 120V to 240V mains supply possible.



## TECHNICAL DATA

Item no.	1001883
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	30 W
Level of inrush current	30 A
Duration of inrush current	40 $\mu$ s
Stroboscopic effect (SVM)	0.06
Lumen	2800/2950 lm
Colour temperature	3000/4000 Kelvin
Beam angle	105 °
Color	black
CRI	80
UGR $\leq$	25
LXXBXX data	L70B50
Service life	25000 h
Light distribution	rotational symmetric

## Light Source

916346	
--------	---

## Accessories

1001952	MEDO 5m suspension , black
1001950	MEDO 5m suspension , white
135250	SUSPENSION SET , for MEDO round pendant, round, black, 5-wire
1001951	MEDO 5m suspension , silver-grey
135251	SUSPENSION SET , for MEDO round pendant, round, white, 5-wire
135254	SUSPENSION SET , for MEDO round pendant, round, silver-grey, 5-wire

Light outlet	direct
Risk Group	1
Height	9.5 cm
Diameter	38 cm
Net weight	2.2 kg
Gross weight	2.9 kg