




MEDO 40 CW AMBIENT

LED Indoor surface-mounted wall and ceiling light, TRIAC, silver-grey 3000/4000K

The high quality MEDO AMBIENT supplements the MEDO series, and impresses with its well thought-out new features: Thanks to its homogeneous, indirect upwards light emission, it generates a decorative AMBIENT effect. A practical switch that provides flexibility, and with the MEDO AMBIENT variant is easy to switch between 3000K and 4000K. The MEDO AMBIENT also excels during installation: The base plate is screwed to the wall or the ceiling, then the body is simply attached to the socket using three clips and can be removed in the same way, of course. The ceiling light can be converted into a pendant using a suspension kit, and is therefore also ideal for rooms with high ceilings. The built-in LED driver makes direct connection to a 120V to 240V mains supply possible.



TECHNICAL DATA

| | |
|----------------------------|----------------------|
| Item no. | 1001885 |
| IP Code | IP 20 |
| Assembly | Surface |
| Assembly details | Ceiling,Wall |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | I |
| Wattage | 30 W |
| Level of inrush current | 30 A |
| Duration of inrush current | 40 µs |
| Stroboscopic effect (SVM) | 0.06 |
| Lumen | 2800/2950 lm |
| Colour temperature | 3000/4000 Kelvin |
| Beam angle | 105 ° |
| Color | grey |
| CRI | 80 |
| UGR ≤ | 25 |
| LXXBXX data | L70B50 |
| Service life | 25000 h |
| Light distribution | rotational symmetric |

Light Source

| | |
|--------|---|
| 916346 |  |
|--------|---|

Accessories

| | |
|---------|---|
| 1001952 | MEDO 5m suspension , black |
| 1001950 | MEDO 5m suspension , white |
| 135250 | SUSPENSION SET , for MEDO round pendant, round, black, 5-wire |
| 1001951 | MEDO 5m suspension , silver-grey |
| 135251 | SUSPENSION SET , for MEDO round pendant, round, white, 5-wire |
| 135254 | SUSPENSION SET , for MEDO round pendant, round, silver-grey, 5-wire |

| | |
|--------------|----------|
| Light outlet | direct |
| Risk Group | 1 |
| Height | 9.5 cm |
| Diameter | 38 cm |
| Net weight | 2.131 kg |
| Gross weight | 2.934 kg |