


## MEDO 40 EL

**LED indoor recessed ceiling light, frameless version, white, 3000/4000K**

The recessed version of the MEDO series fits into every room concept seamlessly thanks to its understated design. The MEDO Frameless combines with the ceiling in a charming way. The light colour can be easily switched between 3000K and 4000K prior to installation using a switch. The integrated premium LED module provides an even lighting effect. Supplemented by an additional driver, the TRIAC recessed variant becomes dimmable and can be integrated in DALI systems.



## TECHNICAL DATA

Item no.	1001902
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	28 W
Maximum ambient temperature	40 °C
Lumen	3100/3300 lm
Colour temperature	3000/4000 Kelvin
Beam angle	105 °
Color	white
CRI	80
UGR ≤	25
LXXBXX data	L70B50
Service life	25000 h
Light distribution	rotational symmetric
Light outlet	direct
Risk Group	1
Height	9.5 cm
Diameter	38 cm
Net weight	2.016 kg

## Light Source

916346	
--------	---

## Accessories

1006120	LED driver , 40W 700/900/1000mA
1005446	LED driver , 40W 700mA PHASE
1004781	LED driver , 21-29.5W 500/600/700mA
1006196	LED driver , 40W 700mA DALI dimmable with RF interface LED driver white DALI
1002424	LED driver MEDO 400 , dimmable DALI/1-10V

Gross weight	2.917 kg
Shape of cut-out	round
Installation depth	13 cm
Installation diameter	39 cm
BIG WHITE Page	170