




ANGOLUX SENSOR WL

LED Outdoor surface-mounted wall light, IP44, anthracite, 3000K

The ANGOLUX SENSOR wall light, which is equipped with a powerful, warm white LED, is available in several colours. The electrical connection of the aluminium luminaire is made directly to the 230V mains supply using the built-in driver. Thanks to its IP44 protection class, the luminaire is suitable for outdoor use. The luminaire is also equipped with a built-in motion sensor. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1001969
IP Code	IP 44
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Number of through-wires	20
Primary nominal voltage	100-240V ~50/60Hz
Secondary power / voltage	240 mA
Safety class	I
Wattage	9.8 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Rated standby power	0.5 W
Level of inrush current	4.5 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0.02
Lumen	750 lm
Colour temperature	3000 Kelvin
Beam angle	100 °
Color	anthracite
CRI	80



Light Source

916333	
--------	---

LXXBXX data	L80B50
Service life	25000 h
Width	17 cm
Height	8.6 cm
Depth	13.5 cm
Net weight	0.634 kg
Gross weight	0.817 kg
BIG WHITE Page	762

