




TRILEDO Double

LED Indoor surface-mounted ceiling light, black, 3000-K, 16W

The rotating and swivelling ceiling light TRILEDO DOUBLE SQUARE CL is made of aluminium and comes in housing colours of white and black. Thanks to its aluminium lamp head, the cone of light can be individually aligned. Equipped with two LED light sources and an LED driver, the luminaire is ready for direct connection to a 230V mains voltage supply.



TECHNICAL DATA

Item no.	1002003
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Level of inrush current	5 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.05
Lumen	1300 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Length	16.25 cm
Width	8.5 cm



Light Source

916451	
--------	---

Height	9.5 cm
Net weight	0.69 kg
Gross weight	0.847 kg
BIG WHITE Page	257

