




PATTA-I

LED outdoor recessed ceiling light, angular DL IP65 black 1800-3000K

The innovative PATTA-I recessed light is suitable for ceiling thicknesses up to 20 mm. Thanks to its IP65 rating, it is suitable for use outdoors and in wet rooms. The light is available in black, white or silver grey, and in a round or square shape. It is fitted with a powerful, dim-to-warm LED, which allows the light colour to be individually adjusted. Thanks to the integrated LED driver, the light can be connected directly to the 230 V mains voltage.



TECHNICAL DATA

Item no.	1002101
IP Code	IP 20 / IP 65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Dim-to-Warm, Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	7.3 W
Level of inrush current	2 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.02
Lumen	44-440 lm
Colour temperature	1800-3000 Kelvin
Beam angle	38 °
Color	black
CRI	95
LXXBXX data	L70B50
Service life	30000 h



Light Source

916436 

Length	8 cm
Width	8 cm
Height	4 cm
Net weight	0.237 kg
Gross weight	0.29 kg
Shape of cut-out	round
Installation depth	6 cm
Installation diameter	6 cm
BIG WHITE Page	244

